



IPH-A807

Ranger IP Video Phone 7" LCD



RANGER



HD Voice & Audio



Android 11 OS



7" Color Display



Wi-Fi(2.4G & 5G)

*All image and specification is subject to change without prior notice.



IPH-A807

Phone Features

16 SIP accounts

Ten-way audio/video mixed conferencing (up to 2 video call)

Call hold, mute, DND

One-touch speed dial, hotline

Call forward, call waiting, call transfer

Redial, call return, auto answer, direct IP call Group listening, SMS, emergency call

Ring tone selection/provisioning

Set date time automatically or manually

Dial plan for each account

RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035) Action URL/URI

Door phone integration

Wireless Access Point (AP mode)

Onscreen keyboard

USB ports (2.0 compliant) for media, storage applications

Notification Center and Control Center

Third party Android application support

Audio Features

HD voice : HD handset, HD speaker

Hearing aid compatible (HAC) handset

Acoustic Shield

Noise Proof

Smart Noise Filtering

Audio codec : Opus, G.722, PCMA, PCMU, G.729A/B, G.726-32,G.723.1, iLBC

DTMF : In-band, Out-of-band (RFC 2833) and SIP INFO

Full-duplex hands-free speakerphone with AEC

VAD, CNG, AEC, PLC, AJB, AGC

Video Features

Support 1080p HD Video

Video codec : H.265, H.264 High Profile, H.264, H.263, VP8

Built-in 2 mega-pixel camera

Directory

Local phonebook up to 10000 entries

Black list

XML/LDAP remote phonebook

Smart dialing

Phonebook search/import/export

Call history : Dialed/received/missed/forwarded

Feature Keys

36 one-touch DSS keys

4 feature keys : Volume Up, Volume down, Home, Back

Interface

Dual-port Gigabit Ethernet

Power over Ethernet (IEEE 802.3af), class 3

1 x USB Type-A port (2.0 compliant)

1 x USB Type-C port (2.0 compliant)

1 x RJ9 (4P4C) handset port

1 x RJ9 (4P4C) headset port

1 x RJ11 port (optional)

1 x HDMI port

1 x Micro SD card slot

1 x Security lock port

IP-PBX Features

Busy Lamp Field (BLF), bridged Line Appearance (BLA) Anonymous call, anonymous call rejection

Hot-desking, voice mail

Call park, call pickup

Intercom, paging

Music on hold

Flexible seating

Call recording

Wi-Fi/Bluetooth

Built-in dual band Wi-Fi :	Network Standard :	IEEE802.11a/b/g/n/ac
	Transmission Rate :	Up to 433 Mbps (dynamic)
	Frequency Range :	2.4GHz/5GHz
Built-in Bluetooth 5.0 :	Bluetooth headset	
	Mobile contacts synchronization	
	Bluetooth call	

Physical Features

Built-in stand with multiple adjustable angles

Wall mountable

External universal AC adapter :	AC 100~240V input and DC 12V/2A output
Power consumption (PSU):	12~24W
Power consumption (PoE):	13W
Operating humidity :	10~90%
Operating temperature :	0~40°C
Storage temperature :	-10~60°C
Weight :	1.8kg
Packing box (L*W*H) :	37.5*26*13.5 cm

Management

Configuration :	Browser/LCD-Menu/auto-provision
Auto provision via HTTP/HTTPS/FTP/TFTP	
Auto-provision with PnP, Zero-sp-touch, TR-069	
Reset to factory, reboot	
Local tracing log export, system log	
Phone lock for personal privacy protection	
Only the administrator can install/uninstall apps via auto provision	
Setup Assistant wizard	

Interface

SIP v1 (RFC2543), v2 (RFC3261)	
Call server redundancy supported	
SIP server/proxy redundancy	
NAT Traversal :	STUN mode
IP assignment :	Static/DHCP
HTTP/HTTPS web server	
Time and date synchronization using SNTP	
DNS-NAPTR/DNS-SRV (RFC 3263)	
QoS :	802.1p/Q tagging (VLAN), Layer 3 ToS DSCP Transport Layer Security (TLS1.3), SRTP, ZRTP
HTTPS certificate manager	
AES encryption for configuration file	
Digest authentication using MD5/MD5-sess IEEE802.1X/OpenVPN	
IPv4/IPv6, LLDP/CDP/DHCP VLAN	